








Checkfluid Symbol	N	J	U	F
Thread Style	NPTF Tapered Pipe Thread	SAE (JIC) 37° Flare Thread	SAE O- Ring Boss Seal, Straight Thread (ORB)	SAE O-Ring Face Seal Thread (ORFS)
Seal Form	D Thread Metal	F Flare Metal	E Boss/C'Bore O-Ring	G O-Ring Face
Male Thread Stud	SAE J476a	SAE J514	SAE J1926-3	SAE J1453
			ISO 11926-3	
Female Thread Port	SAE J476a	SAE J514	SAE J1926-1	SAE J1453
			ISO 11926-1	
Dash Size				
-2	1/8 - 27	5/16 - 24	5/16 - 24	
-3		3/8 - 24	3/8 - 24	
-4	1/4 - 18	7/16 - 20	7/16 - 20	9/16 - 18
-5		1/2 - 20	1/2 - 20	
-6	3/8 - 18	9/16 - 18	9/16 - 18	11/16 - 16
-7			5/8 - 18	
-8	1/2 - 14	3/4 - 16	3/4 - 16	13/16 - 16
-10		7/8 - 14	7/8 - 14	1 - 14
-12	3/4 - 14	1 1/16 - 12	1 1/16 - 12	1 3/16 - 12
-13			1 1/8 - 12	
-14		1 3/16 - 12	1 3/16 - 12	
-16	1 - 11 1/2	1 5/16 - 12	1 5/16 - 12	1 7/16 - 12
-20	1 1/4 - 11 1/2	1 5/8 - 12	1 5/8 - 12	1 11/16 - 12
-24	1 1/2 - 11 1/2	1 7/8 - 12	1 7/8 - 12	2 - 12
-32	2 - 11 1/2	2 1/2 - 12	2 1/2 - 12	

				
Checkfluid Symbol	GB	GC	GD	G (E)
Thread Style	BSPP, O-Ring & Retaining Ring, or Bonded Washer, Parallel Pipe Thread	BSPP, Eolastic Seal Ring, Parallel Pipe Thread	BSPT, Tapered Pipe Thread	BSPP, O-Ring Boss Seal, Parallel Pipe Thread
Seal Form	B Face Metal/O-Ring	C Face O-Ring	D Thread Metal	E Boss/C'Bore O-Ring
Male Thread Stud	ISO 1179-3	ISO 1179-2		
	DIN 3852-2 Type A & B	DIN 3852-11	DIN 3852-2	
			JIS B8363	JIS B2351
Female Thread Port	ISO 1179-1	ISO 1179-1		
	DIN 3852-2 Type X, Y & Z	DIN 3852-2 Type X, Y & Z	DIN 3852-2	
			JIS B8363	JIS B2351
Dash Size				
-2	1/8 - 28	1/8 - 28	1/8 - 28	1/8 - 28
-3				
-4	1/4 - 19	1/4 - 19	1/4 - 19	1/4 - 19
-5				
-6	3/8 - 19	3/8 - 19	3/8 - 19	3/8 - 19
-7				
-8	1/2 - 14	1/2 - 14	1/2 - 14	1/2 - 14
-10				
-12	3/4 - 14	3/4 - 14	3/4 - 14	3/4 - 14
-13				
-14				
-16	1 - 11	1 - 11	1 - 11	1 - 11
-20	1 1/4 - 11	1 1/4 - 11	1 1/4 - 11	1 1/4 - 11
-24	1 1/2 - 11	1 1/2 - 11	1 1/2 - 11	1 1/2 - 11
-32	2 - 11	2 - 11	2 - 11	2 - 11

				
Checkfluid Symbol	MA (MB)	MB	MC	M (E)
Thread Style	DIN O-Ring & Retaining Ring, Metric Straight Thread	O-Ring & Retaining Ring, or Bonded Washer, Metric Straight Thread	Metric Stud Thread	Metric Stud Thread
Seal Form	A (B) Face Metal/O-Ring	B Face Metal/O-Ring	C Face Metal/O-Ring	E Boss/C'Bore O-Ring
Male Thread Stud				SAE J2244-3
			ISO 9974-3	ISO 6149-3
	DIN 3852-1, Type A	DIN 3852-1, Type A & B	DIN 3852-11	DIN 3852-3
Female Thread Port	ISO 9974-1	ISO 9974-1	ISO 9974-1	ISO 9974-1
	DIN 3852-1, Type X, Y & Z	DIN 3852-1, Type X, Y & Z		
Tube OD (mm)				
4	M8 x 1	M8 x 1	M8 x 1	M8 x 1
5	M10 x 1	M10 x 1	M10 x 1	M10 x 1
6	M12 x 1.5	M12 x 1.5	M12 x 1.5	M12 x 1.5
8	M14 x 1.5	M14 x 1.5	M14 x 1.5	M14 x 1.5
10	M16 x 1.5	M16 x 1.5	M16 x 1.5	M16 x 1.5
12	M18 x 1.5	M18 x 1.5	M18 x 1.5	M18 x 1.5
14	M20 x 1.5	M20 x 1.5	M20 x 1.5	M20 x 1.5
16	M22 x 1.5	M22 x 1.5	M22 x 1.5	M22 x 1.5
	M24 x 1.5	M24 x 1.5		
18	M26 x 1.5	M26 x 1.5	M26 x 1.5	M26 x 1.5
20	M27 x 2	M27 x 2	M27 x 2	M27 x 2
22	M30 x 1.5	M30 x 1.5		
	M30 x 2	M30 x 2		M30 x 2
25	M33 x 2	M33 x 2	M33 x 2	M33 x 2
28	M36 x 1.5	M36 x 1.5		
	M36 x 2	M36 x 2		
	M38 x 1.5	M38 x 1.5		
	M39 x 2	M39 x 2		
30	M42 x 2	M42 x 2	M42 x 2	M42 x 2
	M45 x 1.5	M45 x 1.5		
	M45 x 2	M45 x 2		
38	M48 x 2	M48 x 2	M48 x 2	M48 x 2
50	M60 x 2	M60 x 2		M60 x 2